

Email-email dari: **International Journal of Scientific Technology Research (IJSTR)**

Title : **Implementation Of Morphological Segmentation And Local Binary Pattern On K-Nn License Plate Recognition System**

Link Journal : <http://www.ijstr.org/paper-references.php?ref=IJSTR-1119-24735>



I Nyoman Gede Arya Astawa <arya_kmg@pnb.ac.id>

[IJSTR] Submission Acknowledgement

1 messages

Swaminathan <chiefeditor@ijstr.org>
To: i nyoman gede arya astawa <arya_kmg@pnb.ac.id>

Mon, Jul 1, 2019 at 2:50 PM

i nyoman gede arya astawa:

Thank you for submitting the manuscript, "Implementation of Morphological Segmentation and Local Binary Pattern On K-Nn License Plate Recognition System" to IJSTR (International Journal of Scientific & Technology Research). With the onlinejournal management system that we are using, you will be able to track its progress through the editorial process by logging in to the journal website:

Manuscript URL:

<http://www.ijstr.org/index.php/IJSTR/author/submission/6718>

Username: arya_km

If you have any questions, please contact me. Thank you for considering this journal as a venue for your work.

Dr. J.N. Swaminathan
editor-in-chief
IJSTR (International Journal of Scientific & Technology Research)



I Nyoman Gede Arya Astawa <arya_kmg@pnb.ac.id>

[IJSTR] Editor Decision

1 messages

Swaminathan <chiefeditor@ijstr.org>

Sun, Aug 18, 2019 at 1:57 PM

To: i nyoman gede arya astawa <arya_kmg@pnb.ac.id>

Cc: i gusti ngurah bagus catur bawa <caturbawa@pnb.ac.id>, sri andriati asri <sriandriati@pnb.ac.id>, ni made kariati <dekariati@pnb.ac.id>

Dear I Nyoman Gede Arya Astawa:

We have reached a decision regarding your submission to IJSTR (International Journal of Scientific & Technology Research), "Implementation of Morphological Segmentation and Local Binary Pattern On K-Nn License Plate Recognition System".

Our decision is to: Revisions required

In preparing your revised paper, you should pay attention to:

1. An Introduction should contain the following three parts:

- Background: Authors have to make clear what the context is. Ideally, authors should give an idea of the state-of-the art of the field the report is about.

- The Problem: If there was no problem, there would be no reason for writing a manuscript, and definitely no reason for reading it. So, please tell readers why they should proceed reading. Experience shows that for this part a few lines are often sufficient.

- The Proposed Solution: Now and only now! - authors may outline the contribution of the manuscript. Here authors have to make sure readers point out what are the novel aspects of authors work.

Authors should place the paper in proper context by citing relevant papers. At least, 5 references (recently journal articles) are used in this section.

2. Results and discussion section: The presentation of results should be simple and straightforward in style. You should improve your analyzing and also present the comparison between performance of your approach and other researches. Results given in figures should not be repeated in tables. This section report the most important findings, including results of analyses as appropriate. It is very important to prove that your manuscript has a significant value and not trivial.

3. Prepare your figures in high quality and created by yourself (not copy and paste from other parties). All legends, captions ... in your figures MUST in English.

4. Please ensure that: all references have been cited in your text; Each citation should be written in the order of appearance in the text; The references must be presented in numbering. The references must be integrated also with not less than two papers published on 2014-2016 of IJSTR.

Please prepare your revised paper perfectly consider the guide. Please get take a look at: <http://goo.gl/FiPFbF>

You should submit your revised paper through our online system within 8 weeks. Then, your revised paper will be judged for final decision of acceptance or rejection.

Thank you

Best Regards,

Dr. J.N. Swaminathan
editor-in-chief

IJSTR (International Journal of Scientific & Technology Research)



I Nyoman Gede Arya Astawa <arya_kmg@pnb.ac.id>

[IJSTR] Editor Decision

1 messages

Swaminathan <chiefeditor@ijstr.org>
To: I Nyoman Gede Arya Astawa <arya_kmg@pnb.ac.id>

Thu, Oct 3, 2019 at 11:59 AM

Dear I Nyoman Gede Arya Astawa, ST., M.Kom

It is my great pleasure to inform you that your paper has been ACCEPTED and will be published on the IJSTR (International Journal of Scientific & Technology Research)(ISSN 2277-8616, SCOPUS indexed journal).
Congratulations!

In order to cover part of the publication cost, each accepted paper will be charged:

Publication Fee: USD 265

This charge is for the first 8 pages, and if any published manuscript over 8 pages will incur extra charges USD 90 per page

Your paper will be scheduled for forthcoming issue. Please pay the publication fee as soon as possible (within 3 weeks). If you need more time, please send a request to this email. We can give you 5 weeks at the most.

Then, please submit your final paper & payment receipt to this email

I look forward for your response

Sincerely yours,

Dr. J.N. Swaminathan
editor-in-chief
IJSTR (International Journal of Scientific & Technology Research)

Implementation Of Morphological Segmentation And Local Binary Pattern On K-Nn License Plate Recognition System

I Nyoman Gede Arya Astawa, I Gusti Ngurah Bagus Catur Bawa, Sri Andriati Asri, Ni Made Kariati

Abstract: We have seen technological developments lately. Computer science has evolved and implemented into various aspects of life such as health, education, transportation, etc. Intelligent Transportation System (ITS) is one result of the development of computer science. One variant of ITS is the license plate recognition system. Segmentation techniques are usually used to distinguish an image or separate the image into a set of new imagery. The segmentation result of an image is usually a set of new images. In the plate recognition system the result of segmentation is the image of the characters found on the plate. The character image is extracted before entering the character recognition stage. Local Binary Pattern (LBP) is one approach that can be done to feature extraction from an image. In this research, the process of license plate recognition is done by using morphological method as segmentation technique and LBP as its feature extraction.

Index Terms: Plate Recognition, Segmentation, Morphological, Character image, Local Binary Pattern

1. INTRODUCTION

We have seen technological developments lately. Computer science has evolved and implemented into various aspects of life such as health, education, transportation, etc. [1]. Intelligent Transportation System (ITS) is one result of the development of computer science. One variant of ITS is the license plate recognition system [1]. The license plate recognition system implements digital image processing and character recognition in general to identify passing vehicles by reading the license plate automatically [2]. The processes that typically occur in license plate recognition systems are character segmentation on the plate, character recognition and non-characters, feature extraction and number plate matching. Segmentation techniques are usually used to distinguish an image or separate the image into a set of new imagery [3]. Implementation of morphological-based segmentation techniques ever done by [3]. Yadav et al implements a morphological-based image segmentation technique on medical imagery [3]. Morphological transformation uses a dilation function to reduce internal noise and erosion functions to reduce external noise. Li et al also conducted research on 2D-barcode image segmentation using morphological approach [4]. Using the technique, barcodes can be read even if they have a complex background. The segmentation result of an image is usually a set of new images. In the plate recognition system the result of segmentation is the image of the characters found on the plate. The character image is extracted before entering the character recognition stage. Local Binary Pattern (LBP) is one approach that can be done to feature extraction from an image. In research that have done by [5] and [6], they agree if LBP is one of the prominent texture descriptors. LBP has been applied to many applications such as texture recognition, edge detection, etc. The license plate recognition process can be started by segmenting the plate image. The result of the segmentation is a piece of image of the letters contained in the plate image. Next process is to extract the feature using LBP on each image of the letter. In this research, the process of license plate recognition is done by using morphological

method as segmentation technique and LBP as its feature extraction. Therefore, this paper will apply two models, namely feature extraction that have been developed to license plate recognition. Section 2 describes the License plate recognition models. Section 3 describes the analysis and discussion of the results. Finally, conclusions are summarized in Section 4.

2 EXPERIMENTAL DETAIL

The steps in the license plate recognition process are shown in Figure 1. Initially, the plate image enters the segmentation process using a morphological approach. The result of the segmentation is a collection of character images contained in the license plate. The set of images then enters the feature extraction process using the LBP algorithm. The extraction results in this process then become the input parameter of the matching process. In this research, the matching process using k-NN algorithm after passing k-NN process, the result obtained in the form of text from license plate image which become input at the beginning of process. Previously, a database of character training (alphabets and numbers) was created. Creation of the character database is done by collecting the letters A to Z and numbers 0 to 9 obtained from vehicle plates

2.1 Morphological Segmentation

The basics morphological functions are: erosion, dilation, and hit-or-miss [3]. In this study, the image is segmented in the form of binary imagery. Value 0 for black and value 1 for white. All other morphological operations are defined in terms of combination of dilation and erosion, such as opening, closing, etc. [7]. The process of dilation usually causes the object to grow larger, depending on the structure of the element. Conversely, erosion causes the object to become smaller. Hit-or-miss makes it possible to get information about how objects are related to the surrounding environment. The color of segmented images is binary. So, the extraction can be done faster because there are just 2 colors in range, 0 and 1.

2.2 Local Binary Pattern

LBP has been applied to many application areas, such as texture recognition and edge detection. Compared with other texture descriptors, the LBP method has a low computational complexity and is invariant to monotonic illumination changes

* I Nyoman Gede Arya Astawa is currently lecturer in Politeknik state of Bali, indonesia. E-mail: : arya_kmg@pnb.ac.id

[5, 8]. The original LBP of a pixel is generated as follows:

$$LBP_{P,R}(g_c) = \sum_{p=0}^{P-1} S(g_p - g_c) 2^p, s(x) = \begin{cases} 1 & x \geq 0 \\ 0 & x < 0 \end{cases} \quad (1)$$

Where g_c is the value of the central pixel, g_p ($p = 0, \dots, P-1$) represents the value of a neighbor pixel on a circle of radius R and P is the number of sampled neighbors. The neighbors that do not fall at the integer positions can be estimated by bilinear interpolation. LBP has been observed to be a highly efficient feature descriptor for texture classification [9]. A 3x3 mask is used against the neighborhood pixels to define a particular texture and evaluate a LBP. The feature vector is then taken up for processing using the Nearest Neighbor and Support vector machine algorithm to classify the texture images.

3 RESULT AND DISCUSION

The first process is to segment the plate image with the morphological method. Alphabets and numbers already obtained by the morphological method are further extracted features using binary features. Then, the feature matching process used k-NN algorithm. Popular non-parametric method which is used for classification and regression analysis is the k-Nearest Neighbors (k-NN) algorithm. The k-NN algorithm measures the distance between an objective point and a set of points in the data set and assigns the objective (test) point to the class that is most common between its k nearest neighbors around it [9]. The result from segmentation and extraction feature process tested using k-NN algorithm. This is the matching process. In this research, 32 license plate images is tested. There are 255 characters recognized from plate images. Thirty two characters are miss-matched and 218 that are matched. The percentage are 15% for miss-matched character and 85% for matched character. There are several factors that can be a cause of miss-matching. For example, letter 'O' and 'D' looks slightly similar or number '5' and 'S' can be look similar too. This factor can cause the system fail to match the character.

4 CONCLUSION

The license plate recognition process can be done by using morphological method for segmentation and local binary pattern for feature extraction process. Then, the feature matching process used k-NN algorithm. Popular non-parametric method which is used for classification and regression analysis is the k-Nearest Neighbors (k-NN) algorithm. There are 255 characters recognized from plate images. Thirty two characters are miss-matched and 218 that are matched. The percentage are 15% for miss-matched character and 85% for matched character. There are several factors that can be a cause of miss-matching. For example, letter 'O' and 'D' looks slightly similar or number '5' and 'S' can be look similar too. This factor can cause the system fail to match the character.

5 ACKNOWLEDGMENT

The authors would like to thank the department of research and community service center of Politeknik Negeri Bali and the Ministry of Research and Technology of Higher Education of the Republic of Indonesia for the financing of this research.

REFERENCES

- [1] S. S. Tabrizi and N. Cavus, "A Hybrid KNN-SVM Model for Iranian License Plate Recognition," *Procedia Computer Science*, vol. 102, pp. 588-594, 2016/01/01/ 2016, doi: <http://dx.doi.org/10.1016/j.procs.2016.09.447>.
- [2] S. Ktata, T. Khadhraoui, F. Benzarti, and H. Amiri, "Tunisian License Plate Number Recognition," *Procedia Computer Science*, vol. 73, pp. 312-319, 2015/01/01/ 2015, doi: <http://dx.doi.org/10.1016/j.procs.2015.12.038>.
- [3] A. K. Yadav, R. Roy, Rajkumar, Vaishali, and D. Somwanshi, "Thresholding and morphological based segmentation techniques for medical images," in 2016 International Conference on Recent Advances and Innovations in Engineering (ICRAIE), 23-25 Dec. 2016 2016, pp. 1-5, doi: 10.1109/ICRAIE.2016.7939573.
- [4] J. H. Li, W. H. Wang, T. T. Rao, W. B. Zhu, and C. J. Liu, "Morphological Segmentation of 2-D Barcode Gray Scale Image," in 2016 International Conference on Information System and Artificial Intelligence (ISAI), 24-26 June 2016 2016, pp. 62-68, doi: 10.1109/ISAI.2016.0022.
- [5] Z. Pan, Z. Li, H. Fan, and X. Wu, "Feature based local binary pattern for rotation invariant texture classification," *Expert Systems with Applications*, vol. 88, no. Supplement C, pp. 238-248, 2017/12/01/ 2017, doi: <https://doi.org/10.1016/j.eswa.2017.07.007>
- [6] L. Liu, P. Fieguth, Y. Guo, X. Wang, and M. Pietikäinen, "Local binary features for texture classification: Taxonomy and experimental study," *Pattern Recognition*, vol. 62, no. Supplement C, pp. 135-160, 2017/02/01/ 2017, doi: <https://doi.org/10.1016/j.patcog.2016.08.032>.
- [7] Priya and V. S. Verma, "New morphological technique for medical image segmentation," in 2017 3rd International Conference on Computational Intelligence & Communication Technology (CICT), 9-10 Feb. 2017 2017, pp. 1-5, doi: 10.1109/CICT.2017.7977282.
- [8] T. Ojala, M. Pietikainen, and T. Maenpaa, "Multiresolution gray-scale and rotation invariant texture classification with local binary patterns," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 24, no. 7, pp. 971-987, 2002, doi: 10.1109/TPAMI.2002.1017623.
- [9] S. Das and U. R. Jena, "Texture classification using combination of LBP and GLRLM features along with KNN and multiclass SVM classification," in 2016 2nd International Conference on Communication Control and Intelligent Systems (CCIS), 18-20 Nov. 2016 2016, pp. 115-119, doi: 10.1109/CCIntelS.2016.7878212.