




Plagiarism Checker X - Report

Originality Assessment

6%



Overall Similarity

Date: Aug 6, 2023

Matches: 196 / 3284 words

Sources: 16

Remarks: Low similarity detected, check with your supervisor if changes are required.

Verify Report:

Scan this QR Code



Journal of Engineering Design and Technology 62 LOGIC Journal of Engineering Design and Technology Vol. 23 No.1 March 2023; p. 62 - 67 PERFORMANCE ANALYSIS OF PUBLIC TRANSPORT IN GIANYAR REGENCY (Case Study: Batubulan Terminal Route - Ubud) 1) Department of Civil Engineering, Faculty of Engineering, Universitas Hindu Indonesia, Denpasar, Bali 2) Civil Engineering Department, Politeknik Negeri Bali, Bukit Jimbaran, Badung Bali 3) Department of Civil Engineering, Faculty of Engineering and Informatics, Universitas Pendidikan Nasional, Denpasar, Bali Corresponding email 1) : gustu107@gmail.com Ida Bagus Wirahaji 1), I Ketut Sutapa2), I Gede Fery Surya Tapa3), Abstract. The performance of urban public transport plays an important role in accommodating population mobility and realizing sustainable transportation. Public transport performance can be influenced by several factors, including the quality of public transport services and the accessibility of the roads they pass. Service quality concerns arrival frequency, waiting time, travel time, etc. Road accessibility is influenced by the presence of side barriers, such as parking vehicles on the road, cars in and out, slow vehicles, and so on. This study analyzes the exogenous latent variables of service quality and road accessibility that affect the endogenous variables of public transportation performance in the Gianyar Regency, especially on the Batubulan-Ubud Terminal Route. Perception data was collected by distributing 250 questionnaires to people living along the Batubulan-Ubud highway corridor. The data analysis was performed by Statistical Equation Modeling (SEM) AMOS. Validity and reliability tests were carried out using the confirmatory factor analysis (CFA) method. After going through the index modification process, all goodness of fit parameters were fulfilled very well, it was found that the quality of public transportation services had a significant positive effect, with $p\text{-value} = 0.000 < 0.05$, path coefficient 0.498. Road accessibility also has a significant positive effect, with $p\text{-value} = 0.000 < 0.05$, path coefficient 0.308. The quality of public transport services is indicated by the frequency of arrivals, waiting times, and travel times. Road accessibility is indicated by on-street parking and the number of intersections. The number of passengers, driver salaries, and operating duration indicates public transport performance. Keywords : Public

Transport Performance, Service Quality, Road Accessibility 1. INTRODUCTION Public transportation is one of the main actors in sustainable transportation. Increasing the use of public transport systems and reducing the use of private cars is one of the main goals of decision-makers in many countries. The use of the public transport system is closely related to the quality of service. Service quality includes parameters such as convenience, frequency, information systems, and so on. [1]. Other factors that have been identified as attributes of the quality of public transport services are waiting time, travel time, vehicle cleanliness, ease of route, being equipped with driver assistants, and security [2]. The quality of urban public transport services can be measured by several indicators, namely: headway, waiting time, travel time, and speed [3]. Service quality is the biggest subject for both planners and transport operators. The performance of public transport has an important role in accommodating the mobility of the population. In general, service quality is measured by asking about users' perceptions and expectations about several aspects of service quality. Taking into account the level of importance and satisfaction expressed by users [4]. Encouraging people to use public transportation is not an easy task for the government, because public transportation is often considered a bad alternative to car use [5]. To measure and ensure the continuous improvement of the quality of public transport, performance criteria are an important tool for transport operators and focus on their strategic objectives. So far, in developing countries, public transport services have provided substandard quality and limited capacity. Lack of awareness of perceived p-ISSN : 1412-114X e-ISSN : 2580-5649 <http://ojs2.pnb.ac.id/index.php/LOGIC>

LOGIC Jurnal Rancang Bangun dan Teknologi Vol. 23 No. 1 March 2023 Journal of Engineering Design and Technology 63 quality and missing quality management systems are the main causes of poor quality of public transport services. respond to the demand-side needs for accessible, affordable, fast and reliable modes [6]. Road accessibility has always been a major problem in public transportation services and can reduce public interest in using public transportation [7]. One measure of road segment

accessibility is providing access to various activity centers [8]. Accessibility refers to the ability of the community to reach goods, services and activities, which are the ultimate goal of most transportation activities. Many factors affect accessibility, including mobility (physical movement), quality and affordability of transport options, connectivity of transport systems, mobility substitutes, and land use patterns [9]. Service quality and road accessibility are two factors that affect the performance of public transport. Performance is the ability or potential of public transportation to serve the needs of movement in an area, both in the form of transportation of goods and transportation of people. Performance is also the level of achievement or results of the company's work from targets to be achieved or tasks to be carried out within a certain period [10]. Operational indicators of public transport performance include the number of passengers, distance traveled, fuel consumption, and load factor [3]. This research takes the location of the Batubulan-Ubud Terminal route, Gianyar Regency, which is served by microbus vehicles, with a capacity of eight passengers. The routes are: Batubulan-Celuk-Sukawati-BatuanSakah-Peliatan-Mas-Ubud Terminal. From the observations, it can be seen that the public transportation fleet serving this route is very small and only operates in the morning. Meanwhile, this route passes through a road corridor with a relatively dense population, there are side obstacles in the form of parking on the road, vehicles are going in and out, traditional market activities, and vehicles slowing down. People 15 are more likely to use private transportation to fulfill their mobility so transportation becomes worse. This study aims to determine the performance of public transportation on the Batubulan-Ubud Terminal route by analyzing the effect of exogenous variables on service quality and accessibility of the road routes served on the endogenous variable, namely the performance of public transportation. respondent's perception data were analyzed by statistical equation modeling (SEM) AMOS. 2. METHODS Statistical 10 Equation Modeling (SEM) is a strong analytical technique because it considers interaction modeling, nonlinearity, correlated independent variables, measurement errors, correlated error terms, and multiple latent independents where each is measured using many indicators, and one or two latent

dependent variables are also each measured by several indicators. SEM is 4 stronger than using multiple regression, path analysis, factor analysis, time series analysis, and analysis of covariance [11]. Table 1 shows the goodness of fit parameters in SEM. Table 1. Parameter Goodness of Fit [12] [13] No The goodness of Fit Index Cut-off Value Note 1 Chi-square (χ^2) Expected small Testing the level of fit between the sample variance matrix and the model covariance matrix 2 Significance of Probability $\geq 0,05$ When using 12 a 95% confidence level. This indicates that the hypothesis is accepted and the predicted input matrix is not statistically different. 3 CMIN/DF (The Minimum Sample Discrepancy Function) $\leq 2,00$ The fit between the two models. 4 GFI (Goodness of Fit Index) $\geq 0,90$ Nothing but Chi-square divided by DF 5 AGFI (Adjusted Goodness of Fit Index) $\geq 0,90$ Measuring the relative amount of variance and covariance 6 TLI (Tucker Lewis Index) $\geq 0,95$ Its function is the same as the GFI, the difference lies in the adjustment of the DF value to the specified model. 7 1 CFI (Comparative Fit Index) $\geq 0,95$ Comparison between the tested model and the baseline model 8 RMSEA (The Root Mean Square Error of Approximation) $\leq 0,08$ Test the feasibility of a model that is not sensitive to the sample size and complexity of the model This research is an observational study with a survey method, taking a sample of 250 respondents, and using a questionnaire as an instrument for collecting data from the population in Gianyar Regency. The

LOGIC Jurnal Rancang Bangun dan Teknologi Vol. 23 No. 1 March 2023 Journal of Engineering Design and Technology 64 measurement is in the form of public perception of the quality of public transportation services, road accessibility, and public transportation performance. Data analysis used the Amos 10 Structural Equation Modeling (SEM) method, with software ver.22. The measurement scale used is a Likert scale with a score of 1-5, namely: strongly disagree (STS) score 1, disagree (TS) score 2, Slightly agree (US) score 3, Agree (S) score 4, and Strongly Agree (SS) score 5 3. RESULTS AND DISCUSSION 3.1 Validity and Reliability Test Validity and reliability tests were carried out using the confirmation factor analysis (CFA) method. Tables 2 – 4 show the results of the

validity and reliability tests of each latent variable indicator. The value of construct reliability (CR) is obtained from Equation $CR = \frac{(\sum \lambda)^2}{(\sum \lambda)^2 + \sum (1 - \lambda^2)}$ -----

(1) Where: CR : construct reliability λ : loading factor Table 2. The results of the validity and reliability test of the quality of public transportation services (X1) Indicator Service Quality (X1) Notation p Load (λ) CR Arrival frequency is rare X1.1 0.000 0.812 0,906 Not equipped driver assistant X1.2 0.000 0.670 Long waiting time X1.3 0.000 0.728 The vehicle is not clean X1.4 0.000 0.765 The room is not air-conditioned X1.5 0.000 0.657 Small fleet size X1.6 0.000 0.805 Long travel time X1.7 0.000 0.753 Less comfort X1.8

0.000 0.723 Source: Analysis Results (2021) Table 3 Test results of the validity and reliability of Road Accessibility (X2) Indicator Road Accessibility (X2) Notation p Load (λ) CR Lots of vehicle on-street parking X2.1 0.000 0.626 0,845 Many vehicles in and out X2.2 0.000 0.604 There are many intersections X2.3 0.000 0.511 Many vehicles slow down X2.4 0.000 0.754 Frequent switching of currents X2.5 0.000 0.686 Uneven pavement X2.6 0.000 0.631 There are frequent road repairs X2.7 0.000 0.639 There is morning market activity X2.8 0.000 0.630 Source: Analysis Results (2021) Table 4. 2 The results of the

validity and reliability test of Public Transport Performance (Y1) Indicator Public Transport Performance (Y1) NNotation p Load (λ) CR Few passengers Y1.1 0.000 0.702 0,852 Driver's salary below standard Y1.2 0.000 0.605 Short travel distance Y1.3 0.000 0.628 High operating costs Y1.4 0.000 0.604 Exhaust gas/big emissions Y1.5 0.000 0.712 Minor passenger change Y1.6 0.000 0.694 Less fuel consumption Y1.7 0.000 0.628 Short drive operation time Y1.8 0.000 0.603 Source: Analysis Results (2021) The construct reliability

(CR) cut-off value is 0.7, loading factor is 0.50 [14]. 2 From the results of the validity and reliability test using the CFA method, it was found that all indicators had a value of $p = 000 < 0.05$, loading factor (λ) > 0.50 , then all indicators were declared valid. If the value of construct reliability (CR) > 0.7 , then all indicators can be declared reliable.

Model After fulfilling the validity and reliability tests, it is continued to test the model with the goodness of fit, using the maximum likelihood method. Modifications are made so that the model meets several parameters in the goodness of fit. By the table on the modification indices, a reduction or correlation of several indicators is carried out for each latent variable. So that the model is obtained as shown in Figure 1. Figure 1. Diagram of Public Transport Performance Model Source: Analysis Results (2021) After modifying the model, there are only three indicators that can measure the latent variable of service quality (X1), namely: arrival frequency is rare (X1.1); long waiting time (X1.3); and long travel time (X1.7). Two indicators can measure the road accessibility variable (X2), namely: lots of vehicle on-street parking (X2.1) and there are many intersections (X2.3). Three indicators can measure the public transport performance (Y1) variable, namely: Few passengers (Y1.1); driver's salary below standard (Y1.2); standard drive operation time (Y1.8). Table 5 shows that the service quality variable (X1) has a significant effect on public transport performance, with a value of $p = 0.000$, which is smaller than $\alpha = 0.05$. Likewise, road accessibility has a significant effect with the value of $p = 0.000$ which is smaller than $\alpha = 0.05$. Table 5 Regression Weights Latent Variables P Public_transport_performance_Y1 <--- Road_Accessibility_X2 .000 Public_transport_performance_Y1 <--- Service_quality_X1 .000 Source: Analysis Results (2021) 2 Table 6 shows the path coefficient value for the latent variable of service quality (X1), which is 0.498, and the coefficient value. Pathway road accessibility latent variable path (X2) is 0.308. From Table 6, it can be obtained the following public transport performance model: $Y1 = 0.498 X1 + 0.308 X2$

..... (2) Where: X1 :
Service quality X2 : Road accessibility Table 6 Standardized Regression Weights

Arrival_frequency_is_rare_X1.1 <--- Service_quality_X1 .681 Long_waiting_time_X1.3 <---
 Service_quality_X1 .762 Long_travel_time_X1.7 <--- Service_quality_X1 .683
 Lots_vehicle_on-street_parking_X2.1 <--- Road_Accessibility_X2 .650
 There_many_intersection_X2.3 <--- Road_Accessibility_X2 .807 Few_passengers_Y1.1 <---
 -- Public_transport_performance_Y1 .903 Driver's_salary_below_standar_Y1.2 <---
 Public_transport_performance_Y1 .516 Short_drive_operation_time_Y1.8 <---
 Public_transport_performance_Y1 .902 Source: Analysis Results (2021) Parameters 1

of Goodness of Fit Models In this study, eight goodness of fit parameters were tested. The Chi-Square test is useful for testing the relationship or effect of two nominal variables and measuring 12 the strength of the relationship between one variable and another nominal variable. The Chi-square value is very sensitive to the number of samples. The bigger the sample, the bigger the value. Where, with a value of 1 the degree of freedom (DF) = 7 and a significance level of 0.05, the Chi-square table is 16.919 > Chi-square count is 11,850, meaning the model meets. The probability value in this study reached 0.222 > 0.05. Models meet. The significance value is required to increase beyond 0.05 to reduce the calculated Chi-square value so that it does not exceed the Chi-square table. The value of CMIN/DF obtained is 1.317 < 2.00, which fulfills. CMIN/DF 11 is one of the indicators to measure the fitness level of a model. CMIN/DF is nothing but the Chi-square value divided by the DF value. A CMIN/DF value less than 2.00 is an indication of an acceptable fit between the model and the data [12]. The GFI value in this study was 0.988 > 0.900 (very good). GFI is a non-statistical measure that has a range of values between 0 (poor fit) to 1.0 (perfect fit). A high value in the index indicates a better fit and a model is said to be very good if the GFI value is more than or equal to 0.90. The AGFI value in this study was obtained at 0.953 > 0.900, a good overall model fit. AGFI is a criterion that takes into account the weighted proportion of variance in a sample covariance matrix. The recommended acceptance rate is when AGFI has a value equal to or greater than 0.90. A value of 0.95 can be interpreted as a good level-good overall model fit (good) while a value between 0.90 - 0.95 indicates a sufficient-adequate fit level. The TLI value in this study was

0.986 > 0.950. TLI is an alternative incremental fit index that compares a tested model against a baseline model. A value that is very close to 1 or more than 0.95 **1** indicates a very good. The CFI value in this study was 0.996 > 0.950. The magnitude of this index is in the range of values 0 (poor fit) to 1.0 (perfect fit). Values greater than or equal to 0.95 identify the highest level of fit, a very good fit. The RMSEA value in this study was 0.036 < 0.08. RMSEA is another test tool showing the goodness-of-fit that can be expected when the model is estimated in the population [14]. The RMSEA value which **13** is less than or equal to 0.08 is an index for the acceptance of the model which shows a close fit of the model based on the degrees of freedom. Furthermore, the parameters of the goodness of fit Models can be seen in Table 7. Table 7 Results of calculation **1** of goodness of fit parameter. No **Goodness of Fit Index** The calculation results Cut off Value Information 1 Chi-square (χ^2) $11.850 \leq \chi^2 \text{ table } (=16.919)$ Very good 2 Probability $0,222 \geq 0,05$ Very good 3 CMIN/DF $1,317 \leq 2,00$ Very good 4 GFI $0,988 \geq 0,90$ Very good 5 AGFI $0,953 \geq 0,90$ Very good 6 TLI $0,986 \geq 0,95$ Very good 7 CFI $0,996 \geq 0,95$ Very good 8 RMSEA $0.036 \leq 0,08$ Very good Source: Analysis Results (2021) 4. CONCLUSION

Journal of Engineering Design and Technology 67 The results show that all the goodness of fit parameters is fulfilled very well. The exogenous variable of service quality (X1) has a significant positive effect on public transport performance (Y1), with a value of $p = 0.000 < 0.05$, meaning that the higher the service, the higher the performance of public transportation, and vice versa. Service quality is indicated by: arrival frequency (loading factor = 0.681), waiting time (0.762), and travel time (0.683). The exogenous variable of road accessibility (X2) has a significant positive effect **11** on the performance of public transportation, with a value of $p = 0.000 < 0.05$, meaning that the higher the road accessibility, the higher the performance of public transportation, and vice versa. Road accessibility is indicated by: on-street parking (0.650), and intersection (0.807) Public transport performance (Y1) as an endogenous variable is indicated by: **2** the number of

passengers (0.903), Driver's salary (0.516), and operating duration (0.902). The performance of public transportation on the Batubulan-Ubud Terminal route is very poor, which is caused by poor service quality and poor road accessibility. The low quality of service is evidenced by the small arrival frequency, long waiting time, and long travel time. Poor road accessibility is evidenced by the number of vehicles parked on the road, and there are many intersections along the route.

5. REFERENCES [1]. Murat, Y.S., and Cakici, Z. 2017. "Comparative Analysis of Public Transport Users' Perception Targeting Sustainable Transportation." *Engineering Tools and Solutions for Sustainable Transportation Planning*:23. doi: 10.4018/978-1-5225-2116-7.ch004. [2]. Seran, E.N.B.S., and Joewono, T.B. 2015. "Atribut 14 Kualitas Pelayanan Angkutan Publik di Kota Bandung". *Jurnal Teknik Sipil*, 11(2),Oktober 2015, 76-168. [3]. Direktorat Jenderal Perhubungan Darat. 2002. Pedoman Teknik 6 Penyelenggaraan Angkutan Penumpang Umum di Wilayah Perkotaan dan Trayek Tetap dan Teratur. Jakarta: Departemen Perhubungan RI [4]. Eboli, L., and Mazzulla, G. 2008. 7 "Willingness-to-pay of public transport users for improvement in service quality." *European Transport\Transporti Europei* 38:107-118. [5]. Steg, L. 2003. "Can Public Transport Compete with the Private Car?" *IATSS Research* 27(2):27-35. [6]. Ngoc, A.M., Hung, K.V., and Tuan, V.A. 2017. "Towards the Development of Quality Standards for Public Transport Service in Developing Countries: Analysis of Public Transport Users' Behavior." *Transportation Research Procedia* 25 4560–4579. [7]. Chowdhury, S., Zhai, K., and Khan, A. 2016. 16 "University of Auckland Research Repository, Research Space." *Journal of Public Transportation* 19(1):97-113. doi: 10.5038/2375-0901.1.17. [8]. Mavoia, S., Witten, K., McCreanor, T., and O'Sullivan, D. 2012. "GIS-based 5 Destination Accessibility via Public Transit and Walking in Auckland, New Zealand." *Journal of Transport Geography* 20:15-22. [9]. Shah, J., and Andhvaryu, B. 2016. "Public Transport Accessibility Levels for Ahmedabad India". 2 *Journal of Public Transportation*, 19(3), 19-35. [10]. Hazian, M. 2008. Analisis Kinerja Operasional Angkutan Kota di Kota Jambi. Medan: Universitas Sumatera Utara. [11]. Sarwono, J. 2010. "Pengertian Dasar Structural Equation Modeling (SEM)." Universitas

Kristen Krida Wacana. [12]. Ferdinand, A. 8 2006. Structural Equation Modeling Dalam Penelitian Manajemen. Semarang: Badan Penerbit Universitas Diponegoro. [13].

Schumacker, R., dan Lomax, R. 2010. A Beginner Guide to Structural Equation Modeling.

New York: Routledge. [14]. Hair, 9 J., Black, W., Babin, B., dan Anderson, R. 2010.

Multivariate data Analysis: A global perspective 7ed. New Jersey: Pearson Education, Inc.

Sources

1	https://uedufy.com/how-to-interpret-model-fit-results-in-amos/ INTERNET 1%
2	https://etrr.springeropen.com/articles/10.1186/s12544-023-00578-1 INTERNET 1%
3	https://www.emeraldgrouppublishing.com/journal/jedt INTERNET 1%
4	https://www.en.globalstatistik.com/structural-equation-modeling-path-analysis/ INTERNET <1%
5	https://journals.sagepub.com/doi/abs/10.1177/0042098017705846 INTERNET <1%
6	https://www.hukumonline.com/pusatdata/detail/lt5cb5a01b31edf/keputusan-direktur-jenderal-perhubungan-darat-nomor-sk687-aj206-drjd-2002-tahun-2002 INTERNET <1%
7	https://www.scirp.org/(S(czeh2tfqyw2orz553k1w0r45))/reference/referencespapers.aspx?referenceid=2012461 INTERNET <1%
8	https://scholar.google.com/citations?user=qDCMh1AAAAAJ INTERNET <1%
9	https://www.scirp.org/(S(351jmbntvnsjt1aadkposzje))/reference/referencespapers.aspx?referenceid=2336013 INTERNET <1%
10	https://pubmed.ncbi.nlm.nih.gov/28980265/ INTERNET <1%
11	https://www.emerald.com/insight/publication/issn/1726-0531 INTERNET <1%
12	https://online.stat.psu.edu/stat200/lesson/6/6.6 INTERNET <1%
13	https://easystats.github.io/effectsize/reference/interpret_gfi.html INTERNET <1%
14	http://portalgaruda.fti.unissula.ac.id/index.php?ref=browse&mod=viewarticle&article=399840 INTERNET <1%

15

<https://www.tandfonline.com/doi/full/10.1080/01441647.2021.2004262>
INTERNET
<1%

16

<https://www.library.auckland.ac.nz/services/research-support/repositories>
INTERNET
<1%

EXCLUDE CUSTOM MATCHES ON

EXCLUDE QUOTES OFF

EXCLUDE BIBLIOGRAPHY OFF